

Composition Composición	90% SDA - 10% Polyester AT 90% SDA - 10% Poliester AT	Uses Usos
Width Ancho	40 mm	  
Weight Peso	43 g/m ²	  
Thickness Grosor	2 mm	
Finish Acabado	Water repellent. Anti-stain treatment Hidrófugo con tratamiento anti-manchas	
Colour fastness to light Solidez a la luz	7/8 UNE EN ISO 105-B02:2014	Qualities Cualidades
Colour fastness to artificial weathering Solidez del color a la intemperie artificial	4/5 UNE EN ISO 105-B04:1998	  
Colour fastness to rubbing Solidez de las tinturas al frote	4-5/5 UNE EN ISO 105-X12:2016	  
Colour fastness to chlorinated water Solidez de las tinturas al agua clorada	5/5 UNE EN ISO 105-E03:2010	  
Ultraviolet protection factor UPF Factor de protección ultravioleta UPF	50+ AZ/NZS 4399/1996	  
Spray test	5/5 UNE EN ISO 24920	 
Water column mm Columna de agua mm	100 UNE EN ISO 20811	
Breaking Streght Resistencia a la rotura	3200 N UNE EN ISO 13934-1:2013	
Resistance to pilling Resistencia al pilling	4/5 UNE EN ISO 12945-2:2001	
Abrasion resistance (Martindale) Resistencia a la abrasión (Martindale)	20000 UNE EN ISO 12497-2:2016	
Cleaning instructions Manutención	    	 BLEACH friendly

Sensitive values of tolerance +/- 5% Valores susceptibles de tolerancia de +/- 5%



The Agora warranty covers the fabric becoming unserviceable as a result of loss of colour or strength from normal exposure conditions, including sunlight, mildew, rot and atmospheric chemicals, when properly installed, used and maintained. The warranty does not cover labour and installation costs supplied by the dealer. The warranty neither applies against deterioration of any kind due to abusive use, accidental burns, negligence or perforations.

La garantía Agora cubre un anormal deterioro del tejido debido a la pérdida de color o resistencia siempre que existan unas condiciones de exposición normales, incluyendo el sol, moho, putrefacción y químicos de la atmósfera en general, siempre y cuando el tejido haya sido instalado, utilizado y mantenido correctamente. La garantía no cubre los trabajos de instalación del distribuidor. La garantía tampoco cubre, en cualquier caso, el deterioro debido al uso abusivo, quemaduras accidentales, negligencia o perforación.