


Technical Data EGO

Composition Composición	100% Solution Dyed Acrylic 100% Acrílico Tintado en Masa	Uses Usos
Width Ancho	160 cm 63"	  
Weight Peso	580 g/m ² 17.1 oz/y ²	  
Length of rolls Longitud de las piezas	20 ml 21.8 yd	
Finish Acabado	 Eco-Shield No PFAS  Water Repellent Hidrófugo  Ultra Soft Ultra suave  Anti-Stain Antimanchas	Qualities Cualidades
Colour fastness to light Solidez a la luz	8/8 UNE EN ISO 105-B02:2014	 WATER REPELLENT HIDROFUGO  STAIN RESISTANT ANTIMANCHAS  MOULD RESISTANT ANTIMOHOO
Colour fastness to artificial weathering Solidez del color a la intemperie artificial	7/8 UNE EN ISO 105-B04:1997	 EASY TO CLEAN FACIL DE LIMPIAR  UV RESISTANT RESISTENCIA UV  DURABLE DURADERO
Colour fastness to rubbing Solidez de las tinturas al frote	5/5 UNE EN ISO 105-X12:2016	 NO CONDUCTOR NO CONDUCTOR  BREATHABLE TRANSPIRABLE  DISINFECTABLE DESINFECCIONABLE
Colour fastness to chlorinated water Solidez de las tinturas al agua clorada	5/5 UNE EN ISO 105-E03:2010	 DIMENSIONAL STABILITY ESTABILIDAD DIMENSIONAL  SOFT SUAVE  PET FRIENDLY ATO PARA ANIMALES
Ultraviolet protection factor UPF Factor de protección ultravioleta UPF	50+ AZ/NZS 4399/2017 Appendix A	 KID PROOF A PRUEBA DE NIÑOS
Spray test	5/5 UNE EN ISO 24920	 PFAS free  BLEACH friendly
Tear resistance Resistencia al rasgado	Warp Urdimbre 152 N Weft Trama 363 N UNE EN ISO 13937-2:2000	Optional fabric finish Acabado opcional
Slippage resistance Deslizamiento a la costura	Warp Urdimbre 206,61 N Weft Trama 349,40 N UNE EN ISO 13936-1:2004 - 6mm	 WATERPROOF IMPERMEABLE
Tensile strength Resistencia a la tracción	Warp Urdimbre 2100 N Weft Trama 1200 N UNE EN ISO 13934-1:2013	
Resistance to pilling Resistencia al pilling	3/4 UNE EN ISO 12945-2	
Abrasion resistance (Martindale) Resistencia a la abrasión (Martindale)	20000 UNE EN ISO 12497-2:2016	
Shrinkage to washing Encogimiento al lavado	Warp Urdimbre -2% Weft Trama -0% UNE EN ISO 5077:2007	
Flammability Inflamabilidad	UNE 1021 PARTS 1 BS 5852 Cigarette & Match Cal 117	
Cleaning instructions Manutención	    	

Sensitive values of tolerance +/- 5%. Valores susceptibles de tolerancia de +/- 5%.



The Agora warranty covers the fabric becoming unserviceable as a result of loss of colour or strength from normal exposure conditions, including sunlight, mildew, rot and atmospheric chemicals, when properly installed, used and maintained. The warranty does not cover labour and installation costs supplied by the dealer. The warranty neither applies against deterioration of any kind due to abusive use, accidental burns, negligence or perforations.

Waterproof finish: Recommended for cushions and upholstery only. Always use the lamination face inside. Do not expose the coated side to sun or any atmospheric agents.
Acabado Waterproof: Recomendado únicamente para cojines y tapicería. Siempre utilizar la cara laminada en el interior y no exponerla al sol o a las inclemencias del clima.

